

NUVENT SUPERPRO

Nuvent superpro exterior emulsion paint is a premium water based exterior wall emulsion. The paint is formulated with special additives that have antifungal and antifoaming properties which make it suitable for Indian conditions

FEATURES AND BENEFITS

- High Coverage Area
- Eco friendly
- Antifungal agents
- High whiteness
- Ease of application
- Fast colours

RECOMMENDED SURFACES

- Cement Plaster Surface
- Brickwork
- Concrete

PHYSICAL PROPERTIES

Appearance	Pigmented emulsion
Colour	All standard colours
Solid content	50-55 wt%
Wet Film thickness	100 microns
Dry Film Thickness (ASTM D7091 – 13)	60 microns
Specific gravity @ 30°C, gms/ cc (ASTM D1217 – 15)	1.32
Viscosity (ASTM D4287)	540,000 cp
Flash point	100% water based, hence NR
Fire Hazard Class	Non Flammable
Volatile organic Compound (gm/ltr)	< 50 gm/ltr
Shelf Life	When stored in an unopened condition in a cool and dry place shelf life is 12 months

Pack Size: 1 litre, 4 litres, 10 litres, 20 litres

NUVENT SUPERPRO

DIRECTIONS FOR USE

Surface Preparation

- Make sure the surface is cleaned and made dust, oil, debris and wax free
- The loose dust can be removed by scrubbing. For more firm dirt, scrub with a wire brush following by a flush of compressed air pressure and water wash
- If there are patches of old paint, it should be removed. Paint thinners can be used to clean oil like impurities from the surface, allow the surface to dry completely before the application

Application Procedure

- Stir the contents in before use
- Apply two neat coats without dilution by brush or roller at a time interval of 5-6 hours
- Allow the coated surface to air cure fully for 8 hours

APPLICATION DATA

Recommended under coat	Nuvent Superpro exterior wall emulsion primer
Recommended Thinner	Potable water
Dilution Ratio	Maximum 20%
Theoretical Coverage Area	50-60 sqft/ltr for 2 coat at 120 microns DFT*
Drying time	Surface Drying- 45-60 minutes Hard Drying- 4-6 hours
Method of Application	Brush, roller

* Subjected to surface, environmental conditions and application skills

Safety Precautions

- Use nose masks and hand gloves.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- Do not pour leftover coating down the drain or in water course

DISCLAIMER: The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.