

Product Data Sheet

Nuvent Ultralook

PREMIUM QUALITY HIGH GLOSS ENAMEL

Description

Nuvent Ultralook is a specially formulated premium quality enamel. The paint is a single coat system offering high gloss and waterproofing finish to the coated surface.

Features and Benefits

- Pigeon Repellant
- Minimum Surface Preparation
- High Coverage Area
- Ease of application
- Glossy Finish
- Excellent performance at low thickness
- Waterproof surface finish

Technical Data

PROPERTIES	RESULTS
Appearance	Pigmented paint
Colour	All standard shades
Solid content	40-45 wt%
Methods of Application	brush
Theoretical Coverage	8.4 m ² /litre*
Drying Time	6 hours
Recoat frequency	16 hours
Specific gravity @ 30°C, gms/ cc	1.2

* Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

INM Technologies pvt Ltd
 # 13-E/E, 1st phase Kumbalgodu Industrial Area,
 Mysore Road Kengeri Hobli, Bangalore- 560074
 Contact: info@inmtechnologies.com

Standard Application Procedure

Nuvent Ultralook

Method of Application

Surface Preparation

- Make sure the surface is cleaned and made dust, oil, debris and wax free
- The loose dust can be removed by scrubbing. For more firm dirt, scrub with a wire brush following by a flush of compressed air pressure and water wash
- If there are patches of old paint, it should be removed. Paint thinners can be used to clean oil like impurities from the surface
- Allow the surface to dry completely before the application

Application Procedure

- Stir the contents and apply the coating on the surface with a single stroke first horizontally and then vertically
- Let the coating dry for 16 hours (It should not rain during drying hours). Repeat the procedure for the second coat.

Precautions

- Keep the lid tightly closed to reduce evaporation losses and increase shelf life of product
- Do not apply during rains

Safety Information

- Do not breathe vapour or spray. Use solvent mask to avoid inhalation of vapours
- May be harmful if swallowed. In case of ingestion seek immediate medical attention
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- Wear gloves and in case of skin contact immediately wash skin with soap and plenty of water
- Do not pour leftover coating down the drain or in water course

Shelf Life & Storage

When stored in an unopened condition in a cool and dry place shelf life is 12 months

DISCLAIMER: The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.